

ELECTRIC VEHICLE CHARGERS

TESLA EV CHARGER

7KW SINGLE PHASE & 22KW THREE PHASE | EV CHARGER



The Tesla Wall Connector is an efficient and convenient home charging solution that lets you plug your vehicle in overnight and start your day fully charged. The Tesla wall Connector is compatible with Tesla vehicles and most other vehicles.

With a high power output of up to 22kW, the Wall Connector ensures fast charging. For Tesla vehicles, it provides up to 75 kilometers of range per hour of charge. For other electric vehicles, refer to your vehicle manufacturer's guidelines for charging speeds. Its lightweight design allows for versatile installation, suitable for both indoor and outdoor mounting.

Set up and manage your Wall Connector through the Tesla app, connecting it to a local Wi-Fi network to control, schedule, and monitor your charging. Firmware updates are automatically sent to the Wall Connector, enhancing the user experience and introducing new features.

How you benefit:



MODERN & USER-FRIENDLY DESIGN

Easy to install and maintain.
Wall-mounted design.



REMOTE CONTROL & MONITORING

Intelligent monitoring & scheduling.



SAFE OPERATION

IP55 design for indoor/outdoor use.



INNOVATIVE

EV Charger can be configured for single-phase (7kW) or three-phase (22kW) homes.



SOLAHART WARRANTY

Enjoy a 4-year Solahart warranty for residential application and 1-year warranty for commercial use.*

Technical Data	
Performance Specifications	
Nominal Voltage (V)	1-phase 230 V L-N 3-phase 230 V L-L 3-phase 400 V L-L
Current (A)	Maximum 32 A (adjustable by installer)
Grounding Scheme	TN/TT/IT
Frequency	50/60 Hz
Means of Disconnect	External branch circuit breaker
Residual Current Detection	50/60 Hz
Connectivity	Wi-Fi (2.4 GHz, 802.11b/g/n)
Compliance Information	
Agency Approvals	CE, IEC 61851-1 CB
Environmental Specifications	
Operating Temperature Range (°C)	-30°C to 50°C
Storage Temperature	-40°C to 85°C
Enclosure Rating	IP 55: indoor and outdoor use
Mechanical Specifications	
Wall Connector Dimensions	345 mm x 155 mm x 110 mm
Wire Box Bracket Dimensions	250 mm x 120 mm x 50 mm
Weight (including bracket)	6.8 kg
Cable Length	7.3 m



Please visit Tesla website for the latest certificates.

All pictures shown are for reference only. Actual appearance may vary.

* Refer to Tesla Warranty for details of the product warranty and Solahart Owner's Guide & Installation Instructions for installation details.

Solahart Industries Pty Ltd (Solahart) operates a national network of dealers through which independent companies operate dealerships in designated geographic areas. To find your local Solahart Dealer, please visit solahart.com.au. © Solahart (2024). Solahart and the Solahart logo are registered trademarks of Solahart.

Specifications and designs included in this data sheet are subject to change without notice.

Solahart Australia 1300 769 475 | solahart.com.au

Reorder code: SHSD/TESEV

ir5342 TESLA EV Charger_Oct_2024_v8